NSN 5985-00-015-7278

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-015-7278

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Laminated second tubing segment

Flange Quantity:

2

Flange Inside Width:

0.360 inches first flange and 0.364 inches first flange

Flange Inside Height:

0.220 inches first flange and 0.224 inches first flange

Flange Outside Width:

2.500 inches second flange

Flange Outside Height:

2.500 inches second flange

Flange Depth:

0.250 inches second flange

Flange Connecting Hole Diameter:

0.191 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.07

Insertion Loss In Decibels:

0.25

Waveguide Outside Width:

Between 0.358 inches and 0.362 inches

Waveguide Inside Width:

Between 0.279 inches and 0.282 inches

Waveguide Inside Height:

Between 0.139 inches and 0.142 inches

Waveguide Outside Height:

Between 0.218 inches and 0.222 inches

Waveguide Longer Offset Distance:

1.766 feet

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Offset Distance:

0.875 inches

Flexibility:

Rigid single tubing segment

NSN 5985-00-015-7278

Waveguide Assembly - Page 2 of 2



Material:
Copper alloy single tubing segment
Surface Treatment:
Aluminum alloy single tubing segment inside surfaces
Style Designator:
Bend type
Shelf Life:
N/a
Unit Of Measure:
Domilitarization:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0