NSN 5985-00-020-2926

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-020-2926

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges single connection facility

Thread Direction:

Right-hand all flanges single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.900 inches all flanges

Flange Inside Height:

0.400 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Depth:

0.438 inches all flanges

Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 all flanges single connection facility

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches all flanges single connection facility

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Leg Length:

1.375 inches

Waveguide Longer Leg Length:

2.437 inches

NSN 5985-00-020-2926 Waveguide Assembly - Page 2 of 2



Wassanida Cautas Ta Cautas Biotas an
Waveguide Center To Center Distance:
5.375 inches
Waveguide Height:
2.937 inches
Flexibility:
Rigid single tubing segment
Material:
Copper alloy all tubing segment and flange
Surface Treatment:
Silver single tubing segment inside surfaces
Style Designator:
U-bend type
Thread Series Designator:
Unc all flanges single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0