NSN 5985-00-020-5947



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-020-5947 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 2.500 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 0.660 inches **Overall Height:** 1.720 inches **Overall Width:** 0.630 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.840 inches **Operating Tempurature Range:** -54.0 to 95.0 degrees celsius **Voltage Standing Wave Ratio:** 1.50 **Power Rating:** 1.0 watts average **Mounting Facility Screw Thread Series Designator:** Unc **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 1.0 **Overall Attenuation Range In Decibels:** +0.0/+15.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 threaded hole Frequency Range: Between 8.500 gigahertz and 9.600 gigahertz **Overall Attenuation Accuracy In Decibels:** -1.00/+1.00 **Mounting Thread Quantity:** 56 per inch **Adjustment Device Type And Quantity:** 1 slotted screw **Mounting Facility Pattern:**

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

NSN 5985-00-020-5947

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity	/:
----------------------------	----

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0