# NSN 5985-00-027-5918

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-027-5918

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b first flange all connection facilities

#### **Thread Direction:**

Right-hand first flange all connection facilities

# **Tubing Wall Construction Style:**

Seamless single tubing segment

## Flange Quantity:

2

## Flange Inside Width:

3.002 inches second flange

#### Flange Inside Height:

1.502 inches second flange

#### Flange Outside Diameter:

5.313 inches second flange

## Flange Depth:

1.250 inches first flange

## Flange Connecting Hole Diameter:

0.257 inches second flange all connection facilities

# Voltage Standing Wave Ratio:

1.09

# Thready Qty Per Inch (tpi):

20 first flange all connection facilities

#### Maximum Operating Pressure:

5.0 pounds per square inch gage

#### Waveguide Outside Width:

3.000 inches

#### Thread Size:

0.250 inches first flange all connection facilities

#### Waveguide Inside Width:

2.840 inches

#### Waveguide Inside Height:

1.340 inches

# Waveguide Outside Height:

1.500 inches

# Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

#### Flange Style:

Cover type second flange

#### Waveguide Length:

82.000 inches

# NSN 5985-00-027-5918

Waveguide Assembly - Page 2 of 2



Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all flange

Surface Treatment:

Enamel all tubing segment and flange outside surfaces

Style Designator:

Straight type

# **Thread Series Designator:**

Unc first flange all connection facilities

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A073a0