NSN 5985-00-030-8960

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-030-8960

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

2.060 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.880 inches

Overall Height:

2.310 inches

Overall Width:

2.600 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.750 inches

Operating Tempurature Range:

+0.0 to 75.0 degrees celsius

Voltage Standing Wave Ratio:

1.20

Coaxial Connector Series Designation:

Bnc

Power Rating:

500.0 milliwatts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.0

Overall Attenuation Range In Decibels:

+0.0/+10.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 25.000 megahertz and 37.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.10/+0.10

Mounting Thread Quantity:

40 per inch

Adjustment Device Type And Quantity:

1 slotted screw

Mounting Facility Pattern:

Four position rectangular

NSN 5985-00-030-8960

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.112 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0