NSN 5985-00-038-5870

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-038-5870

| Application Design: |
|--|
| Transmission line |
| Body Material: |
| Steel, stainless |
| Body Style: |
| Round, terminal/terminals in opposite surface |
| Body Surface Treatment: |
| Passivated |
| Overall Length: |
| 1.920 inches |
| Overall Diameter: |
| 0.360 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.25 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Wpn |
| Power Rating: |
| 2.0 watts average and 500.0 watts peak |
| Rf Signal Attenuation In Decibels: |
| 40.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +8.0/+12.4 gigahertz |
| Attenuation Accuracy In Decibels: |
| -1.00/+1.00 |
| Temperature Sensitivity Attenuation In Decibels: |
| 0.0001 |
| Connection Type Per Function: |
| Female input and male output |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 12.400 gigahertz |
| Shelf Life: |
| N/a |

NSN 5985-00-038-5870

Fixed Attenuator - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A20000