NSN 5985-00-038-8214

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-038-8214

Application Decima
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.660 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.840 inches
Overall Height:
0.437 inches
Overall Width:
1.720 inches
Unthreaded Mounting Hole Diameter:
0.090 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0 to 20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 1.000 hertz and 8.000 gigahertz
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:

N/a

NSN 5985-00-038-8214

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0