

View Online at <https://aerobasegroup.com/nsn/5985-00-043-1976>

**Thread Class:**

2b mounting facility hole

**Body Style:**

Rectangular

**Overall Length:**

1.000 inches

**Overall Height:**

0.781 inches

**Overall Width:**

0.550 inches

**Frequency Rating:**

20.0 megahertz and 400.0 megahertz single frequency operating

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

0.344 inches single mounting facility pattern

**Operating Temperature Range:**

-55.0 to 100.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.25 single

**Insertion Loss In Decibels:**

0.05 single

**Coaxial Connector Series Designation:**

Bnc

**Rf Power Handling Capability:**

1.0 watts average single

**Minimum Crosstalk Rating In Decibels:**

50.0 single

**Actuator Operating Method:**

Relay

**Actuator Current Type And Rating In Amps:**

0.05 dc

**Actuator Voltage In Volts:**

27.5

**Switch Operation Sequence:**

Makes before breaks

**Pole Quantity:**

1

**Throw Quantity:**

1

**Rf Maximum Voltage Rating:**

30.0 volts rms

**Coupling Position Quantity:**

2

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thread Size:**

0.112 inches mounting facility hole

**Mounting Facility Pattern:**

Two position in-line single mounting facility pattern

**Special Features:**

Connections are unterminated 50 ohm cables

**Material:**

Copper body

**Surface Treatment:**

Zinc body outside surfaces

**Thread Series Designator:**

Unc mounting facility hole

**Terminal Type And Quantity:**

2 cable, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A158a0