NSN 5985-00-044-1754

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-044-1754
Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Round, terminal/terminals in opposite surface
Overall Length:
8.313 inches
Overall Diameter:
0.781 inches
Operating Tempurature Range:
-55.0 to 85.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N .
Power Rating:
5.0 watts average
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 10.0 gigahertz
Attenuation Accuracy In Decibels:
-0.03 to 0.03
Connection Type Per Function:
Female input and male output
Mounting Method:
Terminal
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 1.000 gigahertz and 10.000 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-00-044-1754

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000