NSN 5985-00-050-1416

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-050-1416
Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Round, terminal/terminals in opposite surface
Terminal Material:
Any acceptable
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
2.750 inches
Overall Diameter:
0.600 inches
Voltage Standing Wave Ratio:
1.10
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
500.0 milliwatts average
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+100.0 megahertz
Attenuation Accuracy In Decibels:
-0.60/+0.60
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:

Frequency Range:

2 connector

Between 0.000 hertz and 100.000 megahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-00-050-1416

Fixed Attenuator - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000