

View Online at <https://aerobasegroup.com/nsn/5985-00-052-8573>

Body Style:

Rectangular

Overall Length:

Between 15.590 inches and 15.670 inches

Overall Height:

Between 1.206 inches and 1.226 inches

Overall Width:

0.400 inches

Frequency Rating:

9.5 megahertz and 30.5 megahertz single frequency operating

Unthreaded Mounting Hole Diameter:

Between 0.092 inches and 0.097 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

1.050 inches single mounting facility pattern

Operating Temperature Range:

-54.0/+95.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 single

Insertion Loss In Decibels:

0.10 single

Rf Power Handling Capability:

1.0 watts average single

Minimum Crosstalk Rating In Decibels:

45.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.06 dc

Actuator Voltage In Volts:

Between 20.0 and 30.0

Switch Operation Sequence:

Makes before breaks

Pole Quantity:

2

Throw Quantity:

2

Rf Maximum Voltage Rating:

1.0 kilovolts peak

Coupling Position Quantity:

6

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Metal body

Test Data Document:

97942-580r054 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 wire lead and 2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0