## NSN 5985-00-056-4744

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-056-4744

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
6.510 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.280 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.220 inches
Overall Height:
3.077 inches
Overall Width:
5.063 inches
Unthreaded Mounting Hole Diameter:
0.169 inches
Voltage Standing Wave Ratio:
1.15
Waveguide Flange Type:
Cover
Waveguide Flange Designation:
Ug-39/u
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.0
Overall Attenuation Range In Decibels:
+0.0 to 72.0
Attenuation Variation Method:
Stepped
Mounting Facility Type And Quantity:
4 terminal w/mounting holes
Segment Attenuation Range In Decibels:
+0.00 to 20.00 and +20.00/+40.00 and +40.00/+50.00 and +50.00 to 60.00
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Terminal Type And Quantity:
2 flange
Shelf Life:
N/a
Unit Of Measure:

## NSN 5985-00-056-4744

Variable Attenuator - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A223a0

