

View Online at <https://aerobasegroup.com/nsn/5985-00-060-1859>

Overall Length:

3.690 inches

Overall Height:

2.005 inches

Overall Width:

3.688 inches

Frequency Rating:

3.0 megahertz single frequency insertion loss reference

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

0.875 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.190 inches single mounting facility pattern

Operating Temperature Range:

-67.0 to 165.0 degrees fahrenheit

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.60 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Rf Power Handling Capability:

100.0 watts peak single

Minimum Crosstalk Rating In Decibels:

15.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.8 dc

Actuator Voltage In Volts:

Between 18.0 and 30.0

Switch Operation Sequence:

Makes before breaks

Rf Maximum Voltage Rating:

1500.0 kilovolts peak

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

4 threaded stud

Thread Size:

0.190 inches mounting facility stud

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Aluminum alloy body

Surface Treatment:

Anodize body outside surfaces

Thread Series Designator:

Unf mounting facility stud

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0