## NSN 5985-00-065-1419

Variable Attenuator - Page 1 of 2

**Application Design:** 



View Online at https://aerobasegroup.com/nsn/5985-00-065-1419

Transmission line
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
5.062 inches
Overall Diameter:
5.000 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N and sma
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0 to 20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 1.000 gigahertz and 2.000 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob w/dial and 1 shaft
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.164 inches
Special Features:
Finish: arra blue per mil-f-14072; stainless steel connectors, female type
Terminal Type And Quantity:
2 connector, receptacle
Fsc Application Data:
Antennas, waveguides, and related equipment

## NSN 5985-00-065-1419

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0