NSN 5985-00-066-6829

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-066-6829

| Application Design: |
|---|
| Audio |
| Body Material: |
| Any acceptable |
| Body Style: |
| Rectangular, terminal/terminals on opposite surfaces |
| Body Surface Treatment: |
| Any acceptable |
| Overall Length: |
| 1.625 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.438 inches |
| Overall Height: |
| 1.344 inches |
| Overall Width: |
| 1.531 inches |
| Mounting Hole/stud Quantity: |
| 4 |
| Unthreaded Mounting Hole Diameter: |
| 0.144 inches |
| Schematic Diagram Designator: |
| "t" |
| Input Impedance Rating In Ohms: |
| 500.0 |
| Output Impedance Rating In Ohms: |
| 500.0 |
| Power Rating: |
| 1.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 100.0 |
| Attenuation Accuracy In Decibels: |
| -2.00 to 2.00 |
| Connection Type Per Function: |
| Male input-output |
| Mounting Method: |
| Flange w/mounting hole |
| Terminal Type And Quantity: |
| 5 tab, solder lug |
| Frequency Range: |

Between 0.000 hertz and 20.000 kilohertz

NSN 5985-00-066-6829

Fixed Attenuator - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000