

View Online at <https://aerobasegroup.com/nsn/5985-00-069-3092>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange single connection facility

**Thread Direction:**

Right-hand first flange single connection facility

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Tubing Twist Type:**

Twistable single tubing segment

**Tubing Twist Angle In Deg:**

95.0 single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.003 inches second flange

**Flange Inside Height:**

0.505 inches second flange

**Flange Outside Width:**

1.625 inches second flange

**Flange Outside Height:**

1.625 inches first flange

**Flange Depth:**

0.438 inches second flange

**Flange Connecting Hole Diameter:**

0.169 inches second flange single connection facility

**Voltage Standing Wave Ratio:**

1.15

**Insertion Loss In Decibels:**

10.00

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

1.000 inches

**Thread Size:**

0.164 inches first flange single connection facility

**Waveguide Inside Width:**

0.900 inches

**Waveguide Inside Height:**

0.400 inches

**Waveguide Outside Height:**

0.500 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange single connection facility

**Flange Style:**

Cover type second flange

**Waveguide Length:**

1.500 feet

**Flexibility:**

Flexible all tubing segment

**Material:**

Aluminum alloy all flange

**Surface Treatment:**

Any acceptable all flange outside surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc first flange single connection facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0