NSN 5985-00-070-8132

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-070-8132

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Laminated second tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.175 inches second flange second connection facility

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.494 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Contact type second flange

Waveguide Length:

Between 4.810 inches and 4.830 inches

Flexibility:

Rigid single tubing segment

Material:

Copper alloy single tubing segment

Precious Material And Location:

Internal tubing surface silver

Surface Treatment:

Silver single tubing segment inside surfaces

NSN 5985-00-070-8132

Waveguide Assembly - Page 2 of 2



| Sty | 16 | u | =5 | ıu | aı | u | ч. | _ |
|-----|----|---|----|----|--------|---|----|---|
| | | | | | | | | |

Straight type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0