

View Online at <https://aerobasegroup.com/nsn/5985-00-072-9594>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange and 2.005 inches second flange

Flange Inside Height:

1.002 inches second flange and 1.005 inches second flange

Flange Outside Diameter:

3.625 inches second flange

Flange Depth:

0.938 inches first flange

Flange Connecting Hole Diameter:

0.219 inches all flanges first connection facility and 0.222 inches all flanges first connection facility

Voltage Standing Wave Ratio:

1.10

Maximum Operating Pressure:

40.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges first connection facility

Flange Style:

Cover type second flange

Waveguide Length:

7.312 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber natural single tubing jacket

Surface Treatment:

Oxide film single tubing segment inside surfaces

Style Designator:

Straight type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0