NSN 5985-00-072-9604

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-072-9604

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.000 inches second flange and 1.006 inches second flange

Flange Inside Height:

0.500 inches second flange and 0.506 inches second flange

Flange Outside Width:

1.625 inches second flange

Flange Outside Height:

1.625 inches first flange

Flange Inside Diameter:

1.013 inches first flange and 1.017 inches first flange

Flange Depth:

0.437 inches first flange

Flange Connecting Hole Diameter:

0.151 inches second flange single connection facility and 0.161 inches second flange single connection facility

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.999 inches and 1.002 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

Between 0.899 inches and 0.902 inches

Waveguide Inside Height:

Between 0.399 inches and 0.402 inches

Waveguide Outside Height:

Between 0.499 inches and 1.002 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

1.087 feet

NSN 5985-00-072-9604

Waveguide Assembly - Page 2 of 2

A073a0



Flexibility:
Rigid single tubing segment
Material:
Copper alloy all flange
Surface Treatment:
Enamel single tubing segment outside surfaces and silver single tubing segment outside surfaces and gold single tubing segment outside
surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: