## NSN 5985-00-073-0584

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-073-0584

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b single flange single connection facility

**Thread Direction:** 

Right-hand single flange single connection facility

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

1

#### Flange Inside Width:

1.868 inches single flange and 1.876 inches single flange

## Flange Inside Height:

0.868 inches single flange and 0.876 inches single flange

#### Flange Outside Diameter:

3.625 inches single flange

## Flange Depth:

0.688 inches single flange

## **Maximum Operating Pressure:**

12.0 pounds per square inch gage

## **Waveguide Outside Width:**

Between 2.164 inches and 2.204 inches

#### **Thread Size:**

0.190 inches single flange single connection facility

### Waveguide Inside Width:

Between 1.868 inches and 1.876 inches

## **Waveguide Inside Height:**

Between 0.868 inches and 0.876 inches

#### **Waveguide Outside Height:**

Between 1.164 inches and 1.204 inches

## Flange Connecting Facility And Quantity:

8 threaded hole single flange single connection facility

## Flange Style:

Choke type single flange

## Waveguide Length:

2.219 inches

## **Special Features:**

Waveguide section has a 0.4375 in. Diameter hole through one wall counterbored to 0.283 in. Deep 0.750 in. Dia, 0.456 in. From end

## Flexibility:

Rigid single tubing segment

#### Material:

Aluminum alloy single flange

# NSN 5985-00-073-0584

Waveguide Assembly - Page 2 of 2



_		_			
S	rface	\ Irc	natre	าคท	

Anodize single tubing segment inside surfaces

**Style Designator:** 

Straight type

**Thread Series Designator:** 

Unc single flange single connection facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0