# NSN 5985-00-073-0591

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-073-0591

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

### **Thread Class:**

2b first flange single connection facility

## **Thread Direction:**

Right-hand first flange single connection facility

## **Tubing Wall Construction Style:**

Seamless single tubing segment

## Flange Quantity:

2

#### Flange Inside Width:

2.002 inches second flange and 2.005 inches second flange

#### Flange Inside Height:

1.002 inches second flange and 1.005 inches second flange

#### Flange Outside Diameter:

3.625 inches second flange

#### Flange Depth:

0.938 inches first flange

## Flange Connecting Hole Diameter:

0.203 inches second flange single connection facility and 0.209 inches second flange single connection facility

## Maximum Operating Pressure:

12.0 pounds per square inch gage

## Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

#### **Thread Size:**

0.190 inches first flange single connection facility

## Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

## Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

## Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

## Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

## Flange Style:

Cover type second flange

## Waveguide Length:

5.766 inches

#### Flexibility:

Rigid single tubing segment

## Material:

Aluminum alloy single tubing segment

# NSN 5985-00-073-0591

Waveguide Assembly - Page 2 of 2



Surface Treatment:

Oxide film single tubing segment inside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

Fiig:

A073a0