NSN 5985-00-073-0592

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-073-0592

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange and 2.005 inches second flange

Flange Inside Height:

1.002 inches second flange and 1.005 inches second flange

Flange Outside Diameter:

3.625 inches second flange

Flange Depth:

0.938 inches first flange

Flange Connecting Hole Diameter:

0.203 inches second flange single connection facility and 0.209 inches second flange single connection facility

Maximum Operating Pressure:

40.0 pounds per square inch gage

Waveguide Outside Width:

Between 2.170 inches and 2.174 inches

Thread Size:

0.190 inches first flange single connection facility

Waveguide Inside Width:

Between 1.870 inches and 1.874 inches

Waveguide Inside Height:

Between 0.870 inches and 0.874 inches

Waveguide Outside Height:

Between 1.170 inches and 1.174 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

5.766 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

NSN 5985-00-073-0592

Waveguide Assembly - Page 2 of 2



	tment:

Oxide film all flange inside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0