# NSN 5985-00-073-0626

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-073-0626

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

# **Thread Class:**

2b first flange single connection facility

# **Thread Direction:**

Right-hand first flange single connection facility

#### Bend Angle In Deg:

90.0 third bend e-plane

#### **Tubing Wall Construction Style:**

Seamless single tubing segment

# Flange Quantity:

2

#### Flange Inside Width:

1.503 inches second flange and 1.506 inches second flange

#### Flange Inside Height:

0.753 inches second flange and 0.756 inches second flange

#### Flange Outside Diameter:

3.125 inches second flange

#### Flange Depth:

0.750 inches first flange

# Flange Connecting Hole Diameter:

0.219 inches second flange single connection facility and 0.223 inches second flange single connection facility

# Maximum Operating Pressure:

12.0 pounds per square inch gage

### Waveguide Outside Width:

Between 1.496 inches and 1.504 inches

#### **Thread Size:**

0.190 inches first flange single connection facility

# Waveguide Inside Width:

Between 1.368 inches and 1.376 inches

#### Waveguide Inside Height:

Between 0.618 inches and 0.626 inches

#### Waveguide Outside Height:

Between 0.746 inches and 0.754 inches

# Flange Connecting Facility And Quantity:

6 unthreaded hole second flange single connection facility

#### Flange Style:

Cover type second flange

### Flexibility:

Rigid single tubing segment

# Material:

Aluminum alloy single tubing segment

# NSN 5985-00-073-0626

Waveguide Assembly - Page 2 of 2



Surface Treatment:

Oxide film single tubing segment inside surfaces

# Thread Series Designator:

Unc first flange single connection facility

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A073a0