# NSN 5985-00-073-0626

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-073-0626

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange single connection facility

**Thread Direction:** 

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 third bend e-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

1.503 inches second flange and 1.506 inches second flange

#### Flange Inside Height:

0.753 inches second flange and 0.756 inches second flange

#### Flange Outside Diameter:

3.125 inches second flange

# Flange Depth:

0.750 inches first flange

# Flange Connecting Hole Diameter:

0.219 inches second flange single connection facility and 0.223 inches second flange single connection facility

#### **Maximum Operating Pressure:**

12.0 pounds per square inch gage

# Waveguide Outside Width:

Between 1.496 inches and 1.504 inches

# Thread Size:

0.190 inches first flange single connection facility

#### **Waveguide Inside Width:**

Between 1.368 inches and 1.376 inches

# Waveguide Inside Height:

Between 0.618 inches and 0.626 inches

# **Waveguide Outside Height:**

Between 0.746 inches and 0.754 inches

#### Flange Connecting Facility And Quantity:

6 unthreaded hole second flange single connection facility

# Flange Style:

Cover type second flange

# Flexibility:

Rigid single tubing segment

#### Material:

Aluminum alloy single tubing segment

# NSN 5985-00-073-0626

Waveguide Assembly - Page 2 of 2



	Trea	

Oxide film single tubing segment inside surfaces

**Thread Series Designator:** 

Unc first flange single connection facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0