NSN 5985-00-073-0629

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-073-0629

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange and 2.005 inches second flange

Flange Inside Height:

1.002 inches second flange and 1.005 inches second flange

Flange Outside Diameter:

3.625 inches second flange

Flange Depth:

0.938 inches first flange

Flange Connecting Hole Diameter:

0.219 inches second flange single connection facility and 0.223 inches second flange single connection facility

Maximum Operating Pressure:

12.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Thread Size:

0.190 inches first flange single connection facility

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Waveguide Longer Offset Distance:

3.500 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Offset Distance:

Between 2.454 inches and 2.484 inches

NSN 5985-00-073-0629 Waveguide Assembly - Page 2 of 2



| Flexibility: |
|---|
| Rigid single tubing segment |
| Material: |
| Aluminum alloy single flange |
| Surface Treatment: |
| Oxide film single flange outside surfaces |
| Style Designator: |
| Bend type |
| Thread Series Designator: |
| Unc first flange single connection facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A073a0