NSN 5985-00-073-0711

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-073-0711

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 second bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange and 2.005 inches second flange

Flange Inside Height:

1.002 inches second flange and 1.005 inches second flange

Flange Outside Diameter:

3.625 inches second flange

Flange Depth:

0.813 inches first flange

Flange Connecting Hole Diameter:

0.203 inches second flange single connection facility and 0.209 inches second flange single connection facility

Maximum Operating Pressure:

12.0 pounds per square inch gage

Waveguide Outside Width:

Between 2.002 inches and 2.005 inches

Thread Size:

0.190 inches first flange single connection facility

Waveguide Inside Width:

Between 1.868 inches and 1.876 inches

Waveguide Inside Height:

Between 0.868 inches and 0.876 inches

Waveguide Outside Height:

Between 1.002 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

Flange Style:

Contact type second flange

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all flange

NSN 5985-00-073-0711

Waveguide Assembly - Page 2 of 2



Surface Treatment:

Enamel single tubing segment outside surfaces

Thread Series Designator:

Unc first flange single connection facility

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0