## NSN 5985-00-076-3458



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-076-3458 **Application Design:** Audio **Body Style:** Cylindrical w/side terminals **Overall Length:** 2.062 inches **Body Diameter:** 2.750 inches **Scale Linearity:** Linear **Scale Division Quantity:** 30 **Schematic Diagram Designator:** Bridged "t" **Power Rating:** 0.6 watts average **Mounting Facility Screw Thread Series Designator:** Unc **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.0 **Overall Attenuation Range In Decibels:** +0.0 to 30.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 2 threaded hole **Overall Attenuation Accuracy In Decibels:** -0.30 to 0.30 **Segment Attenuation Range In Decibels:** +0.00 to 30.00

## **Segment Attenuation Accuracy In Decibels:** -0.30 to 0.30 **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 knob

**Mounting Facility Pattern:** 

Two position in-line

**Mounting Facility Screw Thread Diameter:** 

0.164 inches

Impedance Rating In Ohms:

500.0 input-output

## NSN 5985-00-076-3458

Variable Attenuator - Page 2 of 2



Terminal Type A	and Quantity	<b>/</b> :
-----------------	--------------	------------

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0