

View Online at <https://aerobasegroup.com/nsn/5985-00-080-4688>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

6.938 inches

Overall Height:

2.875 inches

Overall Width:

5.500 inches

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

N

Power Rating:

2.0 watts average

Mounting Facility Screw Thread Series Designator:

Unf

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.8

Overall Attenuation Range In Decibels:

+0.0/+10.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

50

Attenuation Per Step In Decibels:

0.2

Mounting Facility Type And Quantity:

3 threaded hole

Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.20/+0.20

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob w/dial

Mounting Facility Pattern:

Isosceles triangle

Mounting Facility Screw Thread Diameter:

0.190 inches

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

4.500 inches

Impedance Rating In Ohms:

50.0 input-output

Test Data Document:

06845-4017479-0701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 connector, coaxial, female and 1 connector, coaxial, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A223a0