

View Online at <https://aerobasegroup.com/nsn/5985-00-080-4692>

Body Style:

Irregular

Overall Length:

2.250 inches

Overall Height:

0.880 inches

Overall Width:

2.040 inches

Frequency Rating:

0.0 megahertz and 900.0 megahertz 1st frequency voltage standing wave ratio25.0 megahertz 1st frequency insertion loss reference0.9 gigahertz and 2.0 gigahertz 2nd frequency voltage standing wave ratio2.0 gigahertz 2nd frequency insertion loss reference0.0 gigahertz and 2.0 gigahertz single frequency operating0.0 gigahertz and 2.0 gigahertz single frequency rf power handling0.0 gigahertz and 2.0 gigahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.140 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

2.250 inches single mounting facility pattern

Operating Temperature Range:

-55.0 to 105.0 degrees celsius

Voltage Standing Wave Ratio:

1.35 2nd

Insertion Loss In Decibels:

0.40 2nd

Coaxial Connector Series Designation:

Tnc

Connector End Design:

Female

Rf Power Handling Capability:

1.0 watts average single

Minimum Crosstalk Rating In Decibels:

35.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.5 dc

Actuator Voltage In Volts:

12.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

15.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Aluminum body

Precious Material And Location:

Connectors rhodium and external surfaces silver

Precious Material:

Rhodium and silver

Surface Treatment:

Rhodium body outside surfaces and silver body outside surfaces

Terminal Type And Quantity:

2 wire hook and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A158a0