

View Online at <https://aerobasegroup.com/nsn/5985-00-083-3100>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches all flanges and 2.005 inches all flanges

Flange Inside Height:

1.002 inches all flanges and 1.005 inches all flanges

Flange Outside Diameter:

3.625 inches all flanges

Flange Depth:

0.375 inches all flanges

Flange Connecting Hole Diameter:

0.219 inches all flanges single connection facility and 0.223 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.10

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges single connection facility

Flange Style:

Cover type all flanges

Waveguide Length:

5.688 inches

Waveguide Center To Center Distance:

6.563 inches

Special Features:

Tubing wall construction can also be seamless or null-point seam

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all flange

Precious Material And Location:

Tubing internal surface silver

Surface Treatment:

Silver single tubing segment inside surfaces

Style Designator:

Offset bend type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0