NSN 5985-00-084-4110

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-084-4110

Application Design: Transmission line **Body Material:** Steel, stainless **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** 3.220 inches **Overall Diameter:** 0.827 inches **Operating Tempurature Range:** -30.0/+70.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 2.0 watts average and 2.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 2.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+3.0 gigahertz **Attenuation Accuracy Reference Frequency:** 3.0 gigahertz **Attenuation Accuracy In Decibels:** -0.20/+0.20 **Connection Type Per Function:** Female input and male output **Unpackaged Unit Weight:** 4.000 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

Frequency Range:

Between 0.000 hertz and 3.000 gigahertz

NSN 5985-00-084-4110

Fixed Attenuator - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000