NSN 5985-00-086-0352

Variable Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-00-086-0352

Printed circuit board
Body Material:
Steel
Body Style:
Irregular
Overall Length:
Between 2.165 inches and 2.445 inches
Overall Height:
Between 1.125 inches and 1.187 inches
Overall Width:
Between 1.375 inches and 1.437 inches
Operating Tempurature Range:
-10.0/+85.0 degrees celsius
Power Rating:
5.8 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+2.86/+17.22
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded stud
Frequency Range:
Between 100.000 kilohertz and 5000.000 kilohertz
Mounting Thread Quantity:
32 per inch
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
600.0 input and 500.0 output
Special Features:
Attenuation varied by frequency
Terminal Type And Quantity:
3 tab, solder lug
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:

NSN 5985-00-086-0352

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0