

View Online at <https://aerobasegroup.com/nsn/5985-00-086-8627>

Thread Class:

2b mounting facility hole

Body Style:

Irregular

Overall Length:

2.000 inches

Overall Height:

1.812 inches

Overall Width:

1.125 inches

Frequency Rating:

200.0 megahertz and 1200.0 megahertz single frequency voltage standing wave ratio

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

0.875 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.688 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+71.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

1.50 single

Coaxial Connector Series Designation:

Bnc

Connector End Design:

Female

Rf Power Handling Capability:

30.0 watts average single

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

1.0 dc

Actuator Voltage In Volts:

26.5

Switch Operation Sequence:

Makes before breaks

Pole Quantity:

1

Throw Quantity:

2

Rf Maximum Voltage Rating:

500.0 volts rms

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.112 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Metal body

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

2 tab, solder lug and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0