NSN 5985-00-086-9125

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-086-9125

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
4.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.340 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.280 inches
Overall Height:
1.687 inches
Overall Width:
2.523 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.169 inches
Operating Tempurature Range:
-28.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.30 and 1.35
Power Rating:
2.0 watts average
Waveguide Flange Type:
Choke
Waveguide Flange Designation:
Ug-1494/u
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+15.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 terminal w/mounting holes
Frequency Range:
Between 7.000 gigahertz and 11.000 gigahertz
Adjustment Device Type And Quantity:

1 shaft

NSN 5985-00-086-9125

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Four position rectangular
Shaft Type:
Round
Terminal Type And Quantity:
2 flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0