NSN 5985-00-087-2547

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-087-2547

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
9.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
8.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches
Overall Height:
2.030 inches
Overall Width:
1.440 inches
Operating Tempurature Range:
-10.0 to 70.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.41
Coaxial Connector Series Designation:
Bnc
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+1.0 to 101.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
9
Attenuation Per Step In Decibels:
1.0 and 2.0 and 3.0 and 5.0 and 10.0 and 20.0 and 20.0 and 20.0 and 20.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 500.000 megahertz
Mounting Thread Quantity:
32 per inch
·
Adjustment Device Type And Quantity: 1 lever
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:

0.164 inches

NSN 5985-00-087-2547

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms	lm	pedance	Rating	In	Ohms
--------------------------	----	---------	--------	----	-------------

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0