NSN 5985-00-087-6251

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-087-6251

Application Design:
Waveguide
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
3.312 inches
Overall Height:
2.562 inches
Overall Width:
1.875 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.730 inches
Distance Between Mounting Facility Centers:
1.125 inches
Operating Tempurature Range:
+0.0 to 55.0 degrees celsius
Coaxial Connector Series Designation:
Bnc
2.10
Power Rating:
Power Rating:
Power Rating: 1.0 watts average
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator:
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels:
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method:
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity:
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity: 10
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels:
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity:
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 2 threaded hole
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range:
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 gigahertz and 2.000 gigahertz
Power Rating: 1.0 watts average Mounting Facility Screw Thread Series Designator: Unc Overall Attenuation Range In Decibels: +0.0 to 10.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 gigahertz and 2.000 gigahertz Overall Attenuation Accuracy In Decibels:

NSN 5985-00-087-6251

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
50.0 input
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Vas - damil/mli

Fiig: A223a0