NSN 5985-00-090-7443

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-090-7443

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

2.875 inches

Overall Width:

3.000 inches

Operating Tempurature Range:

-40.0/+62.0 degrees celsius

Coaxial Connector Series Designation:

Sm

Power Rating:

15.0 watts average and 5.0 kilowatts peak

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.5

Overall Attenuation Range In Decibels:

+0.0 to 20.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 2.900 megahertz and 3.100 megahertz

Overall Attenuation Accuracy In Decibels:

-1.00/+1.00

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.138 inches

NSN 5985-00-090-7443

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0