## NSN 5985-00-094-6289

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-094-6289

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.910 inches
Overall Height:
2.125 inches
Overall Width:
2.125 inches
Distance Between Mounting Facility Centers:
1.125 inches
Operating Tempurature Range:
+0.0 to 65.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Bnc
Power Rating:
500.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.1
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 megahertz and 500.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.10/+0.10
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

1 knob

## NSN 5985-00-094-6289

Variable Attenuator - Page 2 of 2



## Mounting Facility Pattern: Two position in-line Mounting Facility Screw Thread Diameter: 0.164 inches Impedance Rating In Ohms: 50.0 input-output Terminal Type And Quantity: 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: -Demilitarization:

No

Fiig:

A223a0