

View Online at <https://aerobasegroup.com/nsn/5985-00-102-4201>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges single connection facility

Thread Direction:

Right-hand all flanges single connection facility

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Inside Diameter:

1.000 inches all flanges and 1.006 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Voltage Standing Wave Ratio:

1.06

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.997 inches and 1.003 inches

Thread Size:

0.138 inches all flanges single connection facility

Waveguide Inside Width:

Between 0.897 inches and 0.903 inches

Waveguide Inside Height:

Between 0.397 inches and 0.403 inches

Waveguide Outside Height:

Between 0.497 inches and 0.503 inches

Waveguide Longer Offset Distance:

3.250 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Offset Distance:

2.000 inches

Flexibility:

Rigid single tubing segment

Material:

Stainless steel single tubing segment

Surface Treatment:

Nickel alloy single tubing segment inside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc all flanges single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0