

View Online at <https://aerobasegroup.com/nsn/5985-00-102-9363>

Thread Class:

2b mounting facility hole

Body Style:

Irregular

Overall Length:

3.344 inches

Overall Height:

1.250 inches

Overall Width:

2.157 inches

Frequency Rating:

1.0 megahertz and 30.0 megahertz single frequency operating

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.280 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.640 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.500 inches single mounting facility pattern

Operating Temperature Range:

-65.0 to 75.0 degrees celsius

Voltage Standing Wave Ratio:

1.10 single

Insertion Loss In Decibels:

0.10 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Rf Power Handling Capability:

1.0 kilowatts peak single

Minimum Crosstalk Rating In Decibels:

45.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

5.0 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Makes before breaks

Rf Maximum Voltage Rating:

1.0 kilovolts rms

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

3 threaded hole

Thread Size:

0.138 inches mounting facility hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Material:

Steel body

Surface Treatment:

Enamel body outside surfaces

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

2 tab, solder lug and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

FiiG:

A158a0