NSN 5985-00-104-8479

Variable Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-00-104-8479

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
5.500 inches
Overall Height:
6.000 inches
Overall Width:
1.000 inches
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+30.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 connector
2 connector Frequency Range:
Frequency Range:
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity:
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer Terminal Type And Quantity:
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer Terminal Type And Quantity: 2 connector, coaxial, female
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer Terminal Type And Quantity: 2 connector, coaxial, female Fsc Application Data:
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer Terminal Type And Quantity: 2 connector, coaxial, female Fsc Application Data: Antennas, waveguides, and related equipment
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer Terminal Type And Quantity: 2 connector, coaxial, female Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life:
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer Terminal Type And Quantity: 2 connector, coaxial, female Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life: N/a
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer Terminal Type And Quantity: 2 connector, coaxial, female Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life: N/a
Frequency Range: Between 2.000 gigahertz and 6.000 gigahertz Adjustment Device Type And Quantity: 1 micrometer Terminal Type And Quantity: 2 connector, coaxial, female Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure:

Fiig:

A223a0