NSN 5985-00-106-7062

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-106-7062

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.000 inches
Overall Height:
3.000 inches
Overall Width:
1.875 inches
Distance Between Mounting Facility Centers:
1.125 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.50
Coaxial Connector Series Designation:
Bnc
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 megahertz and 1000.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

1 knob

NSN 5985-00-106-7062

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern: Two position in-line Mounting Facility Screw Thread Diameter: 0.164 inches Impedance Rating In Ohms: 75.0 input-output Terminal Type And Quantity: 2 connector, coaxial, female Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A223a0