# NSN 5985-00-106-7064

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-106-7064

Application Design:
Transmission line

Body Style:

Coaxial type

## **Overall Length:**

2.250 inches

#### **Overall Height:**

3.000 inches

**Overall Width:** 

1.875 inches

### **Distance Between Mounting Facility Centers:**

1.125 inches

## Voltage Standing Wave Ratio:

1.20

## **Coaxial Connector Series Designation:**

Bnc

## **Power Rating:**

1.0 watts average

## Mounting Facility Screw Thread Series Designator:

Unc

### **Overall Attenuation Range In Decibels:**

+0.0/+1.0

### **Attenuation Variation Method:**

Stepped

## **Step Position Quantity:**

10

### Attenuation Per Step In Decibels:

0.1

# Mounting Facility Type And Quantity:

2 threaded hole

# Frequency Range:

Between 0.000 megahertz and 500.000 megahertz

# **Overall Attenuation Accuracy In Decibels:**

-0.03/+0.03

# Mounting Thread Quantity:

32 per inch

# Adjustment Device Type And Quantity:

1 knob

# Mounting Facility Pattern:

Two position in-line

# Mounting Facility Screw Thread Diameter:

0.164 inches

# NSN 5985-00-106-7064

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms:

75.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A223a0