

View Online at <https://aerobasegroup.com/nsn/5985-00-110-0343>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

Round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Passivated

**Overall Length:**

2.700 inches

**Overall Diameter:**

0.840 inches

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.15 and 1.20 and 1.25

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

N

**Power Rating:**

5.0 watts average and 1.0 kilowatts peak

**Rf Signal Attenuation In Decibels:**

30.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0 to 4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz

**Attenuation Accuracy Reference Frequency:**

12.4 gigahertz

**Connection Type Per Function:**

Female output and male input

**Unpackaged Unit Weight:**

2.600 ounces

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 12.400 gigahertz

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000