

View Online at <https://aerobasegroup.com/nsn/5985-00-110-3562>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b all flanges all connection facilities

**Thread Direction:**

Right-hand all flanges all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.900 inches all flanges

**Flange Inside Height:**

0.400 inches all flanges

**Flange Outside Width:**

1.625 inches all flanges

**Flange Outside Height:**

1.625 inches all flanges

**Flange Inside Diameter:**

1.422 inches all flanges

**Flange Depth:**

0.438 inches all flanges

**Voltage Standing Wave Ratio:**

1.15

**Insertion Loss In Decibels:**

0.20

**Thready Qty Per Inch (tpi):**

32 all flanges all connection facilities

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

1.000 inches

**Thread Size:**

0.164 inches all flanges all connection facilities

**Waveguide Inside Width:**

0.900 inches

**Waveguide Inside Height:**

0.400 inches

**Waveguide Outside Height:**

0.500 inches

**Flange Connecting Facility And Quantity:**

4 threaded hole all flanges all connection facilities

**Flange Style:**

Choke type all flanges

**Waveguide Length:**

1.696 feet

**Waveguide Center To Center Distance:**

11.840 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Copper single tubing segment

**Precious Material And Location:**

Internal surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Paint all tubing segment and flange outside surfaces

**Style Designator:**

Offset bend type

**Thread Series Designator:**

Unc all flanges all connection facilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0