NSN 5985-00-110-3562

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-110-3562

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.900 inches all flanges

Flange Inside Height:

0.400 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Inside Diameter:

1.422 inches all flanges

Flange Depth:

0.438 inches all flanges

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.20

Thready Qty Per Inch (tpi):

32 all flanges all connection facilities

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

NSN 5985-00-110-3562 Waveguide Assembly - Page 2 of 2



Flange Style:
Choke type all flanges
Waveguide Length:
1.696 feet
Waveguide Center To Center Distance:
11.840 inches
Flexibility:
Flexible single tubing segment
Material:
Copper single tubing segment
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Offset bend type
Thread Series Designator:
Unc all flanges all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0