NSN 5985-00-110-3563

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-110-3563

| Th | rea | d C | lass: |
|----|-----|-----|-------|
| | | | |

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.900 inches all flanges

Flange Inside Height:

0.400 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.20

Thready Qty Per Inch (tpi):

32 all flanges all connection facilities

Maximum Operating Pressure:

30.0 pounds per square inch gage

Thread Size:

0.156 inches all flanges all connection facilities

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Waveguide Length:

1.833 feet

Flexibility:

Flexible all tubing segment

Material:

Beryllium all tubing segment

Precious Material And Location:

Tubing internal surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver all tubing segment inside surfaces

Style Designator:

Offset bend type

NSN 5985-00-110-3563

Waveguide Assembly - Page 2 of 2



| T | hre | ead | Series | Desig | ınator |
|---|-----|-----|---------------|--------|--------|
| - | | | -0 | - 00.9 | |

Unc all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0