## NSN 5985-00-110-3565

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-110-3565

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b all flanges all connection facilities

**Thread Direction:** 

Right-hand all flanges all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.900 inches all flanges

Flange Inside Height:

0.400 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Inside Diameter:

1.422 inches all flanges

Flange Depth:

0.438 inches all flanges

**Voltage Standing Wave Ratio:** 

1.15

**Insertion Loss In Decibels:** 

0.20

Thready Qty Per Inch (tpi):

32 all flanges all connection facilities

**Maximum Operating Pressure:** 

30.0 pounds per square inch gage

**Waveguide Outside Width:** 

1.000 inches

**Thread Size:** 

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

0.900 inches

**Waveguide Inside Height:** 

0.400 inches

**Waveguide Outside Height:** 

0.500 inches

**Waveguide Longer Offset Distance:** 

2.500 inches

## NSN 5985-00-110-3565

Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity:
4 threaded hole all flanges all connection facilities
Flange Style:
Choke type all flanges
Waveguide Offset Distance:
2.500 inches
Flexibility:
Rigid single tubing segment
Material:
Copper single tubing segment
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc all flanges all connection facilities
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** Yes - demil/mli

**Fiig:** A073a0