NSN 5985-00-110-5863

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-110-5863

Unable To Decode:

Internal, rectangular double ridged external, rectangular

Thread Class:

2b all flanges first connection facility

Thread Direction:

Right-hand all flanges first connection facility

Flange Quantity:

2

Flange Inside Width:

0.689 inches all flanges and 0.693 inches all flanges

Flange Inside Height:

0.319 inches all flanges and 0.323 inches all flanges

Flange Outside Width:

1.358 inches all flanges and 1.390 inches all flanges

Flange Outside Height:

1.358 inches all flanges and 1.390 inches all flanges

Flange Depth:

0.235 inches all flanges and 0.255 inches all flanges

Flange Connecting Hole Diameter:

0.096 inches all flanges second connection facility

Voltage Standing Wave Ratio:

1.30

Waveguide Outside Width:

0.791 inches

Thread Size:

0.138 inches all flanges first connection facility

Waveguide Outside Height:

0.421 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges first connection facility

Unable To Decode:

Contact, double ridge type all flanges

Special Features:

Neither flange pressurized

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Surface Treatment:

Enamel all tubing segment and flange outside surfaces

Style Designator:

Three bend type

NSN 5985-00-110-5863

Waveguide Assembly - Page 2 of 2



Marked one end w/arrow and letters inbd

Thread Series Designator:

Unc all flanges first connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0