

View Online at <https://aerobasegroup.com/nsn/5985-00-110-8634>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Tubing Twist Type:**

Straight twist single tubing segment

**Tubing Twist Angle In Deg:**

90.0 single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.017 inches second flange and 1.023 inches second flange

**Flange Inside Height:**

0.507 inches second flange and 0.513 inches second flange

**Flange Outside Width:**

1.673 inches first flange and 1.703 inches first flange

**Flange Outside Height:**

1.673 inches second flange and 1.703 inches second flange

**Flange Depth:**

0.500 inches second flange

**Flange Connecting Hole Diameter:**

0.169 inches first flange single connection facility and 0.172 inches first flange single connection facility

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.10

**Maximum Operating Pressure:**

20.0 pounds per square inch gage

**Waveguide Inside Width:**

Between 1.017 inches and 1.023 inches

**Waveguide Inside Height:**

Between 0.507 inches and 0.513 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole first flange single connection facility

**Flange Style:**

Cover type second flange

**Waveguide Length:**

7.250 inches

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum all flange

**Surface Treatment:**

Enamel all tubing segment outside surfaces

**Style Designator:**

Straight type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0